

CHABLIS

Construction	:	Tufted 1/10 cut pile
Pile Material	:	Faux Silk / 100% PA 6.6 Nylon
Secondary Backing	:	Luxury Backing
Pile Weight	:	ca. 1.31 kg / sq mtr +/- 7.5%
Total Weight	:	ca. 2.32 kg / sq mtr +/- 7.5%
Pile Height	:	ca. 9 mm +/- 7.5%
Total Height	:	ca. 11 mm +/- 7.5%
Usage Classification EN 1307:2014	:	Heavy Domestic / General Commercial
Comfort rating EN 1307:2014	:	LC 5
Static Electricity Charge	:	Anti static
Colour Fastness to Light ISO 105 B02:2013	:	3-4
Rubbing Fastness - Dry ISO 105-X12:2002	:	5
Rubbing Fastness - Wet ISO 105-X12:2002	:	5
Colour Fastness to Water ISO 105 E01:2013	:	5
TOG rating	:	1.26
Burn behaviour BS EN 13501-1:2002	:	Bfl-S1
Stair suitability	:	Yes
Widths	:	4 & 5 mtr +/- 1%
Cut length service	:	Yes
Standard rug sizes	:	No
Bespoke rug service	:	Yes



Matching: This sample may not be from the same batch as current stocks and should be used only as a guide. Equal matching between widths cannot be guaranteed.

Installation: Professional installation is recommended and essential to a good quality underlay. Areas that might receive prolonged exposure to direct sunlight should be protected by the use of blinds or curtains.

Cleaning: Professional cleaning recommended.

Maintenance: To maintain your carpets appearance it is recommended that it is vacuumed at least three times per week to remove particles of dirt and dust, using an upright vacuum cleaner with a rotating brush. It should be noted that overtime foot traffic will flatten the pile in main walkways causing areas of differential wear. This can cause the carpet to show areas of light and dark shading, this happens to all quality carpets and would not be accepted as a basis for any complaint.

ITC Natural Luxury Flooring
 Schering 45, 8281 JW Genemuiden, The Netherlands
 T +31 38 38 611 60

info@itcnaturalluxuryflooring.com
www.itcnaturalluxuryflooring.com

ITC Natural Luxury Flooring Ltd
 12 Hay Hill, Mayfair, London, W1J 8NR, UK
 T 0162 253 4041