

QUALITY
ORDER CODE

DATE: 10/07/2018
REPLACES: 21/12/2010

WIDTH (±) cm

TYPE

GAUGE AND TYPE

TEXTURING

DYEING/PRINT METHOD

PILE COMPOSITION

FIBRE BRAND

WOOLMARK

MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²

TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm

TOTAL HEIGHT (±) mm

NUMBER OF KNOTS (±) m²

STITCHES OVER WIDTH (±) / 10 cm

STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm

REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m

PILE IN/OUT

LANO CLASSIFICATION

BEDROOM

LIVING ROOM

OFFICE

CASTOR ROLLCHAIRS DOMESTIC USE

CASTOR ROLLCHAIRS PROFESSIONAL USE

STAIRS DOMESTIC USE

STAIRS PROFESSIONAL USE

ELECTROSTATIC BEHAVIOUR

UNDERFLOOR HEATING

BATH ROOM

NON-FRAY

PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER

DIBT

UPEC n°

CLASSIFICATION

HQE

EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

GRANIT SB
GRT

± 400 & 500
COLLECTION
1/10" LOOP PILE

PIECE DYED

PA

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 460
± 1.630

± 3,0
± 5,0
± 173.360
± 39,40
± 44,00

±
±

± 28
PILE OUT

✓

✓

✓

✓

✓

✓

✓

ANTISTATIC

✓

✓

✓

CDEOC87E

19863
Z-156.601-957 - PA 6 / 111 / FS

04/106
U3P3E1C0

✓

CL. 33
Commercial Heavy



LC1

Cfl-s1

LOW RADIUS

QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 22



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

± 0,01

(±)

250Hz

± 0,03

(±)

500Hz

± 0,07

(±)

1000Hz

± 0,15

(±)

2000Hz

± 0,34

(±)

4000Hz

± 0,58



SOUND ABSORPTION

(±)

α_w

EN ISO 11654

± 0,15

THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,072



TOG rating

(±)

± 0,72

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤ 2000



SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤ 10 E11

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤ 10 E11

LIGHTFASTNESS

ISO 105-B02

≥ 6

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 4

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 4

WATERFASTNESS STAINING

ISO 105-E01

≥ 4

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE
FROM

AVAILABLE
FROM

COLOURS

<u>SB 400</u>	<u>GRT</u>	<u>SB 500</u>
110	CARMINE	110
121	CORAL 1	121
134	ROSE 4	134
220	ACORN	220
257	MAGNOLIA 7	257
269	CAMEL 9	269
270	ALMOND	270
300	MAHOGANY	300
400	COFFEE	400
410	LEATHER	410
570	MOSS	570
680	JUNIPER	680
700	NAVY	700
730	AZURE	730
764	WEDGWOOD 4	764
793	MIDNIGHT 3	793
802	EBONY 2	802
810	CHARCOAL	810
819	CHARCOAL 9	819
820	SLATE	820
827	SLATE 7	827
842	MOONSHINE 2	842
843	MOONSHINE 3	843
858	MOONBEAM 8	858

<u>SB 400</u>	<u>GRT</u>	<u>SB 500</u>
---------------	------------	---------------



WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE

(24)

(24)

