

SANCERRE

Construction	:	Tufted 1/10 cut pile
Pile Material	:	Faux Silk / 100% PA 6.6 Nylon
Secondary Backing	:	Luxury Backing
Pile weight	:	ca. 1.60 kg / sq mtr +/- 7.5%
Total weight	:	ca. 2.50 kg / sq mtr +/- 7.5%
Carpet Thickness	:	ca. 12 mm +/- 7.5 %
Usage Classification EN 1307:2014	:	Heavy Domestic / General Commercial
Comfort rating EN 1307:2014	:	LC 5
Static Electricity Charge	:	Anti static
Light ISO 105 B02:2013	:	4-5
Rubbing - Dry ISO 105 X12	:	4-5
Rubbing - Wet ISO 105 X12	:	4-5
Water ISO 105 E01 : 2013	:	4
Water Stains EN1307/EN15115	:	4-5
TOG rating	:	1.15
Burn behaviour BS EN ISO 9239-1:2002	:	Bfl-S1
Stair suitability	:	Light use
Widths	:	4 & 5 mtr +/-1 %
Cut length service	:	Yes
Standard rug sizes	:	No
Bespoke rug service	:	Yes

Matching: This sample may not be from the same batch as current stocks and should be used only as a guide. Equal matching between widths cannot be guaranteed.

Installation: Professional installation is recommended and essential to a good quality underlay. Avoid exposure direct sunlight. Areas that might receive prolonged exposure to direct sunlight should be protected by the use of blinds or curtains.

Cleaning: Professional cleaning recommended.

Maintenance: To maintain your carpets appearance it is recommended that it is vacuumed at least three times per week to remove particles of dirt and dust. It should be noted that overtime foot traffic will flatten the pile in main walkways causing areas of differential wear. This can cause the carpet to show areas of light and dark shading, this happens to all quality of velour carpets and would not be accepted as a basis for any complaint.

ITC Natural Luxury Flooring
Schering 45
8281 JW Genemuiden
The Netherlands

T +31(0)38 38 611 60
F +31(0)38 38 611 61
E info@itcnaturalluxuryflooring.com
W www.itcnaturalluxuryflooring.com