

QUALITY		DATE:	28/03/2017
ORDER CODE		REPLACES:	24/06/2013
WIDTH	(±) cm		
TYPE			
GAUGE AND TYPE			
TEXTURING			
DYEING/PRINT METHOD			
PILE COMPOSITION			
FIBRE BRAND			
WOOLMARK			
MOTHPROOF			
PRIMARY BACKING			
SECONDARY BACKING			
PILE WEIGHT	(±) gr/m ²		
TOTAL WEIGHT	(± 15%) gr/m ²		
EFFECTIVE PILE HEIGHT	(±) mm		
TOTAL HEIGHT	(±) mm		
NUMBER OF KNOTS	(±) m ²		
STITCHES OVER WIDTH	(±) / 10 cm		
STITCHES OVER LENGTH	(±) / 10 cm		
REPEAT TUFTING DESIGN L/W	(±) mm		
REPEAT PRINTING DESIGN L/W	(±) mm		
ROLL LENGTH	(±) m		
PILE IN/OUT			
CLASSIFICATION			
BEDROOM			
LIVING ROOM			
OFFICE			
CASTOR ROLLCHAIRS DOMESTIC USE			
CASTOR ROLLCHAIRS PROFESSIONAL USE			
STAIRS DOMESTIC USE			
STAIRS PROFESSIONAL USE			
ELECTROSTATIC BEHAVIOUR			
UNDERFLOOR HEATING			
BATH ROOM			
NON-FRAY			
PERSONAL COMPUTER			
PRODIS-NUMBER			
GUT-NUMBER			
DIBT			
UPEC n°			
CLASSIFICATION			
HQE			
EN 1307			
ADDITIONAL CHARACTERISTICS EN 1307			
LUXURY CLASS			
FIRE RESISTANCE EUROPE		EN 13501-1	
FIRE RESISTANCE UK		BS 4790	
CLASSIFICATION			
CLASSIFICATION BS7131			

LOUNGE SB
ZEO

± 400 & 500
COLLECTION (WE)
1/10" TWIST

PIECE DYED

100% TRIEXTA
SMARTSTRAND

WOVEN SYNTHETIC SECONDARY BACKING

± 1.490
± 2.480

± 7,5
± 10,0
± 173.360
± 39,40
± 44,00

±
±

± 50
PILE IN

✓
✓
✓

✓

✓

7D4EBEDD

Z-156.601-1299 - Mohawk PTT / 1610

Cl. 23 / Cl. 32
Domestic Heavy / Commercial General



LC5



Cl-s1



QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 29



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

±

(±)

250Hz

± 0,04

(±)

500Hz

± 0,12



(±)

1000Hz

± 0,3

(±)

2000Hz

± 0,56

(±)

4000Hz

± 0,74

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

± 0,25

THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,147



TOG rating

(±)

± 1,47

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

<

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5-6

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3-4

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 5

WATERFASTNESS STAINING

ISO 105-E01

≥ 4-5

LABEL CE



ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

COLOURS

AVAILABLE
FROM

AVAILABLE
FROM

SB 400	ZEO	SB 500
081	PURPLE 1	081
091	AUBERGINE 1	091
120	CRIMSON KISS	120
131	ROSE 1	131
141	OLD ROSE 1	141
151	SAHARA 1	151
190	MALT CHOCOLATE	190
221	ACORN 1	221
251	MAGNOLIA 1	251
260	NATURAL WICKER	260
371	GOLD 1	371
381	BRONZE 1	381
430	SABLE	430
451	SAND 1	451
460	HAZELNUT	460
470	CHESTNUT	470
551	APPLE MINT 1	551
611	IVY 1	611
681	JUNIPER 1	681
761	WEDGWOOD 1	761
781	STEEL 1	781
820	DOMINO	820
830	ELEPHANT	830
841	MOONSHINE 1	841
850	URBAN OBSESSION	850
871	SILVER 1	871
880	EGYPTIAN COTTON	880

SB 400	ZEO	SB 500
890	IVORY	890

(28)

(28)



WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE