

QUALITY
ORDER CODE

DATE: **26/02/2021**
REPLACES: 21/12/2010

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

ZEN SB/FS
ZEN

± 400
COLLECTION
1/10" SAXONY

PIECE DYED

PA

NON WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.000
± 2.160

± 6,0
± 8,5
± 200.940
± 39,40
± 51,00

±
±

± 25
PILE IN

✓

✓

✓

✓

✓

✓

✓

ANTISTATIC

✓

✓

✓

BD4DAE7B

20759

Z-156.601-952 - PA 6.6 / 121

12/291

U3sP3E1C0

✓

CL. 33

Commercial Heavy








LC3




Bfl-s1



QUALITY

| | | | | | |
|--------------------------------|-----------|------------|------------------|---------|---|
| IMPACT SOUND INSULATION | (±) dB | | ISO 140/8 | ± 28 |  |
| SOUND ABSORPTION | (±) | α_s | ISO 354 - 125 Hz | ± 0,01 |  |
| | (±) | | 250Hz | ± 0,02 | |
| | (±) | | 500Hz | ± 0,12 | |
| | (±) | | 1000Hz | ± 0,3 | |
| | (±) | | 2000Hz | ± 0,49 | |
| | (±) | | 4000Hz | ± 0,5 | |
| SOUND ABSORPTION | (±) | α_w | EN ISO 11654 | ± 0,25 | |
| THERMAL RETENTION | (±) m²K/W | | ISO 8302 | ± 0,112 |  |
| TOG rating | (±) | | | ± 1,12 | |
| PERMANENTLY ANTISTATIC | (±) volt | | ISO 6356 | ≤ 2000 |  |
| SURFACE RESISTANCE RoT | (±) ohm | | ISO 10965 | ≤ 10 E9 | |
| SURFACE RESISTANCE RdT | (±) ohm | | ISO 10965 | ≤ 10 E9 |  |
| LIGHTFASTNESS | | | ISO 105-B02 | ≥ 5-6 | |
| RUBBINGFASTNESS DRY | | | ISO 105 X12 | ≥ 4 | |
| RUBBINGFASTNESS WET | | | ISO 105 X12 | ≥ 4 | |
| WATERFASTNESS CHANGE IN COLOUR | | | ISO 105-E01 | ≥ 4 | |
| WATERFASTNESS STAINING | | | ISO 105-E01 | ≥ 3-4 | |

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

COLOURS

AVAILABLE FROM

AVAILABLE FROM



| SB/FS 400 | ZEN |
|-----------|--------------|
| 041 | ANEMONE 1 |
| 054 | CROCUS 4 |
| 061 | HEATHER 1 |
| 109 | RUBY 9 |
| 110 | CARMINE |
| 124 | CORAL 4 |
| 141 | OLD ROSE 1 |
| 164 | MUSCAT 4 |
| 182 | RUM 2 |
| 204 | CHOCOLATE 4 |
| 261 | CAMEL 1 |
| 271 | ALMOND 1 |
| 280 | HAVANNA |
| 301 | MAHOGANY 1 |
| 311 | RUST 1 |
| 423 | CORNSTALK 3 |
| 434 | BAMBOO MAT 4 |
| 451 | SAND 1 |
| 511 | GRASS 1 |
| 544 | CURRY 4 |
| 552 | APPLE MINT 2 |
| 624 | SAVANNA 4 |
| 711 | ATLANTIC 1 |
| 734 | AZURE 4 |
| 742 | OCEAN 2 |
| 762 | WEDGWOOD 2 |
| 774 | SAPPHIRE 4 |

| SB/FS 400 | ZEN |
|-----------|------------|
| 782 | STEEL 2 |
| 790 | MIDNIGHT |
| 800 | EBONY |
| 810 | CHARCOAL |
| 812 | CHARCOAL 2 |
| 820 | SLATE |
| 830 | ASH |
| 832 | ASH 2 |
| 840 | MOONSHINE |
| 850 | MOONBEAM |
| 862 | GRANITE 2 |
| 871 | SILVER 1 |
| 872 | SILVER 2 |

(40)