

## TECHNICAL INFORMATION



### Physical properties:

Total weight: 400g/m<sup>2</sup> (nominal) Vinyl  
 Weight: 310g/m<sup>2</sup> (nominal) Substrate  
 Type: Nonwoven Fabric Substrate  
 weight: 90g/m<sup>2</sup> (nominal)



### Other specifications available:

Tensile Strength: MD 40 N/cm (nominal)  
 TD 30 N/cm (nominal)  
 Tear Strength: 4500 mN (nominal)



### Roll size:

130cm x 30m - cut lengths available



### Pattern Repeat:

Reverse hang, straight match



### Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations. Euroclass B - s2, d0.  
 Class A ASTM E-84 Tunnel Test.



### Adhesive:

Fabric backed vinyls - Newmor Heavy.  
 Varies with substrate - please enquire.



### Bacteria Resistance:

Contains an active Fungicide.



### Light Fast:

Excellent Light Fastness  
 BS EN ISO 105-B02 7/8

### LRV = Light reflective value

Available on request

### Specifications:

Conforms to requirements of BS EN 15102, BS EN 259 and WA Quality Standard W-101.

### Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test.  
 Resistant to temporary staining of oils, fats, mild acids and alkalis.

### Quality Assurance:

Our management system and production procedures comply with ISO9001: 2015, the internationally recognised Quality Standard.

### Availability:

Every product stocked in depth.  
 5.00pm deadline for next day delivery.  
 (UK only)

### Origin:

Designed, coloured, manufactured and stocked in the UK.

### Warranty:

Newmor offers a five year warranty against manufacturing defects.  
 Full details available on application.

### Samples:

Larger samples are readily available on request.

### Maintenance:

Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself. Also able to withstand the use of chlorine releasing agent solutions.



MADE IN GREAT BRITAIN  
 British Product | Global Support